

FOAMCORE PIPING SYSTEMS

REINFORCED TO BEAR THE FORCE.

High load-bearing Foamcore Piping Systems for durable and effective drainage.



PIPES
As per IS:16098

PRODUCT RANGE
Pipes: 110mm to 315mm



EXTENSIVELY USED IN



WASTE DRAINAGE LINE

APPLICATIONS

- Underground drainage.

The outer and innermost layers give the pipe a great load bearing capacity, the middle layer provides firmness to the overall pipe structure.

MAJOR ADVANTAGES

- Lighter than solid wall PVC but stronger.
- Easy underground installation.
- Compatibility with other drainage and sewerage products.
- Cost-effective.
- Long life due to improved strength.
- Anti rodent

JOINTING METHOD

- Solvent Cement Joint
- Elastomeric Sealing Ring



PIPE DIMENSIONS

Pipe Size (mm)	Mean Outside Diameter (mm)		Wall Thickness (mm)					
			SN2 (SDR 51)		SN4 (SDR 41)		SN8 (SDR 34)	
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
110	110.00	110.40	-	-	2.80	3.30	3.20	3.70
160	160.00	160.50	3.20	3.70	4.00	4.60	4.70	5.40
200	200.00	200.60	3.90	4.50	4.90	5.60	5.90	6.70
250	250.00	250.80	4.90	5.60	6.20	7.00	7.30	8.30
315	315.00	316.00	6.20	7.00	7.70	8.70	9.20	10.40