

# SWR PIPING SYSTEMS

## SAY GOODBYE TO LEAKAGES.

Leakproof SWR piping systems with world-class triple lip rubber ring.



**PIPES**  
As per IS:13592

**FITTINGS**  
As per IS:14735

### PRODUCT RANGE

Pipes: 40mm to 160mm

Fittings: Solvent - 40mm to 160mm

Rubber Ring - 75mm, 90mm, 110mm & 160mm



### Types of Pipe Available:

Type A



VENTILATION  
PIPE WORK



RAIN WATER  
DISCHARGE &  
HARVESTING

Type B



SOIL AND WASTE  
DISCHARGE SYSTEM

## EXTENSIVELY USED IN



HOSPITALS



RESIDENTIAL



HOTELS

## APPLICATIONS

- Inside & outside building drainage systems including ventilation.
- Rain water discharge & harvesting for residential and commercial buildings/complexes.
- Industrial buildings and public utilities.

## MAJOR ADVANTAGES

- Lightweight but strong.
- Compatible with other drainage products.
- Easy to install.
- Smooth bore.
- Cost-effective.
- World-Class Seals ensures long term sealing performances against leakages.\*\*
- Long life.

**\*\*Trubore world-class seals**

## JOINTING METHOD

- Elastomeric Sealing Ring
- Solvent Cement Joint

## PIPE DIMENSIONS

Pipe Size (mm)	Mean Outside Diameter (mm)		Wall Thickness (mm)			
			Type 'A'		Type 'B'	
	Min	Max	Min	Max	Min	Max
40	40.00	40.30	1.80	2.20	3.20	3.80
50	50.00	50.30	1.80	2.20	3.20	3.80
63	63.00	63.30	1.80	2.20	3.20	3.80
75	75.00	75.30	1.80	2.20	3.20	3.80
90	90.00	90.30	1.90	2.30	3.20	3.80
110	110.00	110.40	2.20	2.70	3.20	3.80
160	160.00	160.50	3.20	3.80	4.00	4.60

## FITTINGS RANGE

### SWR FITTINGS WITH RUBBER RING JOINT

**BEND 45°**



75mm to 160mm

**BEND 87.5°**



75mm to 160mm

**BEND WITH DOOR**



75mm to 160mm

**CLEANSING PIPE**



75mm to 160mm

**COUPLER**



75mm to 160mm

**DOUBLE Y**



75mm & 110mm

**DOUBLE Y WITH DOOR**



75mm & 110mm

**REDUCER**



110mmx75mm & 160mmx110mm

**REDUCING TEE**



110mm X 75mm & 160mm X 110mm

**REDUCING TEE WITH DOOR**



160mm X 110mm

**SINGLE TEE**



75mm to 160mm

**SINGLE TEE WITH DOOR**



75mm to 160mm

**SINGLE Y**



75mm to 160mm

**SINGLE Y WITH DOOR**



75mm to 160mm

**REDUCING Y**



110mm X 75mm

### SWR FITTINGS WITH SOLVENT JOINT

**ACCESS / SOCKET PLUG\***



50mm to 110mm

**BEND 45°**



75mm to 160mm

**BEND 87.5°**



75mm to 160mm

**BEND WITH DOOR**



75mm to 160mm

**CLEANSING PIPE**



75mm to 160mm

**COUPLER**



75mm to 160mm

**DOOR CAP**



75mm & 110mm

**DOUBLE TEE**



75mm & 110mm

**DOUBLE TEE WITH DOOR**



75mm & 110mm

**DOUBLE Y**



75mm & 110mm

**DOUBLE Y WITH DOOR**



75mm & 110mm

**MULTI FLOOR TRAP (WITH JALI) 4" HT**



110mm x 75mm

**MULTI FLOOR TRAP (WITHOUT JALI) 4" HT**



110mm x 75mm

**NAHANI TRAP WITH JALI**



110mm x 75mm

**NAHANI TRAP WITHOUT JALI**



110mm x 75mm

**PIPE CLIP\***



75mm to 160mm

**P TRAP**



110mm x 110mm & 125mm x 110mm

**P TRAP SHORT**



110mm x 110mm

**REDUCER**



110mm x 75mm & 160mm x 110mm

**REDUCING TEE**



110mm x 75mm & 160mm x 110mm

**REDUCING TEE WITH DOOR**



160mm x 110mm

**REDUCING Y**



110mm x 75mm

**ROUND JALI**



110mm x 110mm

**SINGLE TEE**



75mm to 160mm

**SINGLE TEE WITH DOOR**



75mm to 160mm

**SINGLE Y**



75mm to 160mm

**SINGLE Y WITH DOOR**



75mm to 160mm

**VENT COWL**



75mm & 110mm

Images shown here are for representation purpose only, actual product may vary.

